

COMMERCIAL FLOODLIGHT

Technical Data Sheet

Created on: 16-12-2019



Address:

Luceco plc,
Caparo House,
103 Baker Street,
London, W1U 6LN.

Telephone:

+44 (0)1952 238 100

Email Address:

info@luceco.com

Commercial Floodlight

- Die-cast aluminium housing with polycarbonate lens for increased durability
- Symmetric wide area lens distribution
- Wall mounting bracket supplied with 0.75M cable

Overview

Code	Lumens	Wattage	Luminaire Efficacy	Equivalent
LFC92B40	9200	100	92	250W
LFC190B40	19000	200	95	400W

Construction & Installation

	Length (mm)	Width (mm)	Height (mm)	Fixing Centre W (mm)	Weight(kg)	Ingress Protection	Impact Resistance	Projected Area m ²
LFC92B40	65	380	235	260	3.0	IP65	IK07	0.09
LFC190B40	70	380	380	260	5.1	IP65	IK07	0.12

Technical Information

	Life time hours	Temperature range	In-Rush Current (A,US)	Earth Leakage mA	Voltage Range	Frequency	Approval	Electrical Class	Power Factor
LFC92B40	30000	25°C 40°C	TBC	TBC	220V-240V	50-60	CE	1	0.9
LFC190B40	30000	25°C 40°C	TBC	TBC	220V-240V	50-60	CE	1	0.9